



SELF-PRIMING PUMPS



ETM

X · PRO



Pressure regulating knob with anti-tampering device

Manopola regolazione pressione con dispositivo anti-manomissione



LW-K 250

PRO VERSIONS

Pump with 3 integral ceramic pistons. Oil sight glass. Brass pump heads

VERSIONI PRO

Pompa con 3 pistoni in ceramica integrale. Visore livello olio. Testate in ottone



GXR

X VERSIONS

Comet electrical pump with three axial pistons arranged vertically with pump at the bottom and an all-metal construction without any plastic used for the structural components

VERSIONI X

Elettropompa Comet a tre pistoni assiali disposta in verticale con pompa in basso e costruzione interamente in metallo, senza materiale plastico nei componenti strutturali



FOR MORE INFO:
MAGGIORI INFORMAZIONI:



GENERAL FEATURES · CARATTERISTICHE GENERALI

- Easy to transport thanks to a practical top grip and anti-vibration supports
- Induction 2-pole motor (2800 rpm) on ETM 150 X model
- 4-pole motor (1400 rpm) on ETM 150 PRO model
- Built-in professional unloader valve with ejector
- EASY START device
- Total Stop system
- Rotary switch
- Motor thermal protection
- Semplicità di trasporto mediante confortevole impugnatura superiore ed appoggio su supporti antivibranti
- Motore a 2 poli a induzione (2800 giri/min) per modello ETM 150 X
- Motore a 4 poli (1400 giri/min) per modello ETM 150 PRO
- Valvola di regolazione professionale integrata con eiettore
- Dispositivo EASY START
- Dispositivo Total Stop
- Interruttore rotativo
- Protezione termica del motore
- Uso semiprofessionale gravoso (uso professionale per ETM 150 PRO)

TECHNICAL FEATURES · CARATTERISTICHE TECNICHE

CODE CODICE	MODELS MODELLI	PUMP POMPA													
			Ph	V	Hz	bar	MPa	bar	MPa		I/h	HP			
9055 0016	ETM 150 X	GXR	1	230	50	150	15	30 ÷ 135	3 ÷ 13,5	280 ÷ 600	3,0	2,2	2,9	25	26 x 47 x 37
9055 0011	ETM 150 PRO	LW-K 250	1	230	50	150	15	30 ÷ 135	3 ÷ 13,5	280 ÷ 600	3,0	2,2	2,9	35	26 x 47 x 37

STANDARD EQUIPMENT · DOTAZIONE STANDARD

X 	PRO 	X
GC 201 gun with protection <i>Pistola GC 201 con protezione</i>	GC 251 gun with protection <i>Pistola GC 251 con protezione</i>	Lance with adjustable jet, with nozzle <i>Lancia getto regolabile con ugello</i>
PRO 	PRO 	X PRO
Bent lance with detergent head, without nozzle <i>Lancia angolata con testina detergente, senza ugello</i>	15° spray nozzle, 1/4" MEG connection <i>Ugello con getto a lama 15° attacco 1/4" MEG</i>	R1 1/4" 10 m rubber delivery hose kit <i>Kit tubo mandata in gomma 10 m R1 1/4"</i>